

# CLAIMS

1. A method comprising steps of:  
 covering a first semiconductor die area, said first semiconductor die area including  
 a first dielectric area, said first dielectric area having a first permeability;  
 5 interspersing a permeability conversion material in a second area of said  
 semiconductor die, said second semiconductor die area including a second dielectric area,  
 said permeability conversion material having a second permeability, said second  
 permeability being higher than said first permeability.

2. The method of claim 1 wherein said covering step comprises covering said  
 first semiconductor die area with photoresist.

3. The method of claim 1 wherein said first dielectric area comprises silicon  
 dioxide.

4. The method of claim 1 wherein said first dielectric area comprises a low-k  
 dielectric.

5. The method of claim 1 wherein said second dielectric area comprises  
 20 silicon dioxide.

6. The method of claim 1 wherein said second dielectric area comprises a low-  
 k dielectric.

7. The method of claim 1 wherein said permeability conversion material is selected from the group comprising of nickel, iron, nickel-iron alloy, and magnetic oxide.

5 8. The method of claim 1 wherein said step of interspersing is performed by implanting said permeability conversion material in said second area of said semiconductor die.

9. The method of claim 1 wherein said step of interspersing is performed by sputtering said permeability conversion material on said second area of said semiconductor die.

10. The method of claim 1 further comprising a step of patterning a conductor within said second dielectric area, said conductor forming an inductor.

11. The method of claim 10 wherein said conductor is selected from the group consisting of copper, aluminum, and copper-aluminum alloy.

12. The method of claim 10 wherein said conductor is patterned as a square spiral.

13. The method of claim 10 wherein said permeability conversion material is selected from the group comprising of nickel, iron, nickel-iron alloy, and magnetic oxide.

14. The method of claim 10 wherein said step of interspersing is performed by implanting said permeability conversion material in said second area of said semiconductor die.

5

15. The method of claim 10 wherein said step of interspersing is performed by sputtering said permeability conversion material on said second area of said semiconductor die.

16. A method comprising steps of:  
patterning a conductor within a dielectric;  
interspersing a permeability conversion material in said dielectric, wherein said permeability conversion material has a permeability greater than a permeability of said dielectric.

10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995

17. The method of claim 16 wherein said dielectric comprises silicon dioxide.

18. The method of claim 16 wherein said dielectric comprises a low-k dielectric.

20

19. The method of claim 16 wherein said permeability conversion material is selected from the group comprising of nickel, iron, nickel-iron alloy, and magnetic oxide.

20. The method of claim 16 wherein said step of interspersing is performed by implanting said permeability conversion material in said dielectric.

21. The method of claim 16 wherein said step of interspersing is performed by sputtering said permeability conversion material on said dielectric.

22. The method of claim 16 wherein said conductor is selected from the group consisting of copper, aluminum, and copper-aluminum alloy.

23. The method of claim 16 wherein said conductor is patterned as a square

spiral.

24. A structure in a semiconductor chip, said structure comprising:

a first area of a dielectric, said first area of said dielectric having a first permeability;

a second area of said dielectric, said second area of said dielectric having a second permeability, said second permeability being higher than said first permeability;

a conductor patterned in said second area of said dielectric.

25. The structure of claim 24 wherein said dielectric is silicon dioxide.

26. The structure of claim 24 wherein said dielectric is a low-k dielectric.

~~27. The structure of claim 24 wherein said second permeability is achieved by interspersing a permeability conversion material within said second area of said dielectric, said permeability conversion material having a third permeability, said third permeability being greater than said first and second permeabilities.~~

5

Pub  
BT

~~28. The structure of claim 27 wherein said permeability conversion material is selected from the group consisting of nickel, iron, nickel-iron alloy, and magnetic oxide.~~

D1

29. The structure of claim 24 wherein said conductor is selected from the group consisting of copper, aluminum, and copper-aluminum alloy.

30. The structure of claim 24 wherein said conductor is patterned as a square spiral.

31. A structure in a semiconductor chip, said structure comprising:  
a dielectric having a first permeability;  
a permeability conversion material having a second permeability, said permeability conversion material being interspersed within said dielectric, wherein said second permeability is greater than said first permeability;  
an inductor comprising a conductor patterned within said dielectric, said conductor having first and second terminals, said first and second terminals of said conductor being respectively first and second terminals of said inductor.

Sub  
C2

32. The structure of claim 31 wherein said dielectric is silicon dioxide.

33. The structure of claim 31 wherein said dielectric is a low-k dielectric.

5 34. The structure of claim 31 wherein said permeability conversion material is  
DI selected from the group consisting of nickel, iron, nickel-iron alloy, and magnetic oxide.

35. The structure of claim 31 wherein said conductor is selected from the group  
consisting of copper, aluminum, and copper-aluminum alloy.

36. The structure of claim 31 wherein said conductor is patterned as a square  
spiral.

Add  
P27